



A Benny Lee Company

LP & LPBC-25 SERIES

DESKTOP POWER SUPPLY

LP SERIES FEATURES

- Filtered and Regulated
- Over Temperature Protection
- Adjustable Output Voltage
- Overload and Over Voltage Protection
- Battery Back-up Operation with LPBC-25
- Compatible with all LPH Hoods
- ISO 9001 / UL Recognized / CSA Approved
- LP-14N model includes a cord with Motorola SAE connector



SPECIFICATIONS

Model Number	Output Current (Amps)	Output Voltage VDC	Input Voltage VAC	Weight (lbs)
LP-10	10	13.8	110 or 220	2.9
LP-14	14	13.8	110 or 220	2.9
LP-14N	14	13.8	110 or 220	2.9
LP-18	18	13.8	110 or 220	3.1
LP-25	25	13.8	110 or 220	3.4

1.75" H x 7" W x 7.62" D



LPBC-25 FEATURES

- Dual shottky diodes provide protective isolation and seamless transfer to battery when power goes down. No relays to fail.
- LPBC-25 automatically provides float charge, battery maintenance when power is restored.
- Provides battery backup/charging for any power supply up to 20 Amps



5" H x 2" W x 4" D

BATTERY RECOMMENDATION

- LPBC-25 @ 12 VDC - 50 Amp/hr
- LPBC-25 @ 24 VDC - 30 Amp/hr

SPECIFICATIONS

Model Number	Amps (Max)	Input Voltage VDC	Output VDC
LPBC-25	20	10.5 ~ 30	10.5 ~ 30