



©ENTRI SERIES

Comparison Chart



Features	Site Centri	Site Graph	Site Scout
Factory Configured - AC Volt	1	2	1
Factory Configured - DC Volt	4	5	2
Factory Configured - DC Amp	1	1	1
Digital Input	4	10 (Opto-Isolated)	2 (Opto-Isolated)
Digital Output	4	4 (Opto-Isolated)	0
Relay Out	-	4 (Form C)	4 (Form C)
Temp Sen	External	1 In /1 External	1
SNMP	v1, v2, v3	v1, v2, v3	v1, v2, v3
HTTP(S)	HTTP	HTTP	HTTP, HTTPS*
OTA Firmware Updates	Ethernet	Ethernet	Ethernet/Wireless
Web Based Data Graphing	-	Internal	-
Analog to Digital Conversion (ADC)	12 Bit	24 Bit	12 Bit
Time stamped, continuous data logging	x	x	x
Ethernet Port	x	x	x
Remote Reboot	x	x	x
Automated Recovery	x	x	x
Self Generated Web Page	x	x	x
User Customized Inputs & Alarms	x	x	x
SMTP/POP 3 e-mail Alerts	x	x	x
Email	1	6	6
Secure TCP/IP Communications			x
Wi Fi			x
Touch Screen			x
Internal Secure Web Server			x
12C, Smbus, Pmbus Header			Optional
MQTT, AWS, MODBUS			Optional

*HTTPS available by request